

R&S[®] SFU-K221

T-DMB/DAB Streams

Specifications

The scope of T-DMB/DAB stream library applications depends on the R&S[®]SFx-K22 TRP player option of the R&S[®]SFx.

T-DMB/DAB streams	sequences in line with ETS 300 799 TRP player (R&S [®] SFx-K22)	see description of option for details required for playout	
Transmission	transmission mode	depending on loaded stream and transmission mode setting used in the R&S [®] SFU, R&S [®] SFE, R&S [®] SFE100	
	stream format	ETI (NI, G.703)	
Signal set	streams	DAB, T-DMB and DAB	
	number of streams	21 DAB streams and 288 T-DMB/DAB streams	
	content	depending on loaded stream	
	playback	endless	
	video and audio	not seamless	
	DAB		
	service	DAB service	
	content	tones, audio, audio and data, CISPR tests	
	DAB mode	1	
	audio sampling rate	48 kHz	
	tones		
	subchannel	subchannel 1	
	sequence	100 Hz, 1 kHz, 10 kHz sine, 16 tones	
	mode	stereo	
	convolutional coding	UEP	
	data rate	128 kbps	
	duration	12 s to 59 s	
	audio		
	subchannel	subchannel 1	
	sequence	music (Bach), live scenario (applause and park scene), synthetic audio, frequency sweep	
	mode	stereo	
	convolutional coding	UEP	
	data rate	128 kbps	
	duration	7 s to 49 s	
	audio and data		
	subchannel	subchannels 1 to 9	
sequence	audio and data		
audio	1 kHz, full scale to 0 dB		
subchannel	subchannel 1		



Signal set (cont.)	audio and data (cont.)		
	mode	stereo	
	data rate	192 kbps	
	mode	stereo	
	convolutional coding	UEP	
	data	All 0	
	subchannel	subchannels 2 to 9	
	data rate	8/16/32/64/96/128/384 kbps	
	convolutional coding	EEP	
	duration	120 s	
	CISPR		
	test scenario	in line with CISPR 13, CISPR 14	
	subchannel	subchannel 1, subchannels 1 to 3	
	DAB mode	1	
	protection level	3, 3-A	
	sequence	1 kHz (6 dB, digital zero, 0 dB), 1 kHz (full scale to 0 dB), 1 kHz (6 dB), 1 kHz (silent to digital zero)	
	mode	stereo	
	convolutional coding	UEP	
	data rate	128 kbps, 192 kbps	
	duration	120 s	
	T-DMB/DAB ¹		
	service	one T-DMB service and one DAB service	
	subchannel	subchannel 1	
	DAB mode	1, 2, 3, 4	
	protection level	1-A, 1-B, 2-A, 2-B, 3-A, 3-B, 4-A, 4-B	
	total data rate	256 kbps to 1152 kbps	
	T-DMB encoding		
	video	ISO/IEC 14496 (MPEG-4) Part 10 AVC Baseline Profile Level 1.3	
	subchannel	subchannel 1	
	content	diver sequence	
	frame rate	25 frames/s, 30 frames/s	
	video resolution	QVGA, CIF	
	data rate	136/151/240/255/256/268/320/332/360/ 358/384/400/410/460/462/527/540/592/ 620/877/1023 kbps	
	DAB encoding		
	audio	ISO/IEC 14496 (MPEG-4) Part 3 BSAC Baseline Profile Level 1.3, MPEG-4 HE-AAC v1, MPEG-4 HE-AAC v2	
	content	music of diver sequence	
	subchannel	subchannel 1	
	level	0 dB	
	mode	stereo	
	data rate	56 kbps	
	Stream support	R&S [®] SFU	full support of all streams
		R&S [®] SFE	full support of all streams
		R&S [®] SFE100	full support of all streams

¹ Audio Specific Config (ASC) data flag contains sampling rate value of 96000 Hz.

Rohde & Schwarz GmbH & Co. KG

www.rohde-schwarz.com

Regional contact

Europe, Africa, Middle East

+49 89 4129 137 74

customersupport@rohde-schwarz.com

North America

1-888-TEST-RSA (1-888-837-8772)

customer.support@rsa.rohde-schwarz.com

Latin America

+1-410-910-79 88

customersupport.la@rohde-schwarz.com

Asia/Pacific

+65 65 13 04 88

customersupport.asia@rohde-schwarz.com

R&S[®] is a registered trademark of Rohde & Schwarz GmbH & Co. KG

Trade names are trademarks of the owners | Printed in Germany (sk)

PD 5214.2862.22 | Version 01.00 | January 2010 | R&S[®]SFU-K221

Subject to change

© 2010 Rohde & Schwarz GmbH Co. KG | 81671 München, Germany